

Adjustability

Hole size Ø59mm

Product Specifications

Input Voltage	AC 220 -240V, 50-60Hz	
Fixture Power	7W	10W
Driving Current	200 mA	250 mA
Lumen Output*	318 lm	426 lm
Fixture Efficiency	45.4 lm/w	42.6 lm/w
CRI	90	
Color Temperature	2700K/3000K/4000K	
Beam Angle	15°	
Source Type	Citizen COB LED	
Power Factor	-	
Shielding Angle	60°	
Control Method	Not dimmable, Phase-cut dimming, 0/1-10V dimming, DALI dimming	

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	<19
Product Dimensions	Ø69*80 mm
Hole Size	Ø59 mm
Weight	0.39 kg
Package Size	L11.7*11*13.5 cm
Carton Size	24PCS/CTN, L46.5*W37.5*H29.5 cm

Safety Class	Class II
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L90/B10-Ta25°
IP Rating	IP20
Housing Material	Die-cast Aluminium
Housing Color**	RAL 9006, RAL 9016, RAL 9005
Warranty	3 years

*Lumen output measured @ 2700K, 15° optics, ambient temperature 25°C

**RAL 9006 White aluminium, RAL 9016 Traffic white, RAL 9005 Jet black


Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
01.0411	YW - Matt white YB - Matt black XX - Customized Color	007 - 7W 010 - 10W	90	27 - 2700K 30 - 3000K 40 - 4000K	15 - 15°	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector


Example: 01.0411YW007902715F0

Photometric Distribution


7W 15° 2700K



10W 15° 2700K



Assembly Indication



Accessories

