

### Product Specifications

Input Voltage	AC 220 -240V, 50-60Hz		
Fixture Power	30W	45W	60W
Size	L1198xW200xH50mm	L1788xW200xH50mm	L2388xW200xH50mm
Lumen Output*	2850 lm	4275 lm	5700 lm
Fixture Efficiency	95.0 lm/w	95.0 lm/w	95.0 lm/w
CRI	90		
Color Temperature	3000K/4000K/5000K		
Beam Angle	MPO		
Source Type	Citizen COB LED		
Power Factor	>0.9		
Shielding Angle	60°		
Control Method	Not dimmable, 0/1-10V dimming, DALI dimming		

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	/
Product Dimensions	L1198/1788/2388*W200*H50 mm
Weight	/
Package Size	/
Carton Size	/

Safety Class	Class I
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L90/B10-Ta25°
IP Rating	IP20
Housing Material	Extruded Aluminium
Housing Color**	RAL 9006, RAL 9016, RAL 9005, RAL 1035
Warranty	3 years

\*Lumen output measured @ 2700K, ambient temperature 25°C

\*\*RAL 9006 White aluminium, RAL 9016 Traffic white, RAL 9005 Jet black, RAL 1035 Pearl beige


### Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
06.4040	YW - Matt white YB - Matt black XX - Customized Color	030 - 30W	90	30 - 3000K 40 - 4000K 50 - 5000K	MPO	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector

Example: 06.4040YW0309030MPOF0

## Photometric Distribution

30W MPO 3000K



## Accessories



Suspension Kit