



*Customizable length

Product Specifications

Input Voltage	AC 220 -240V, 50-60Hz
Fixture Power	10W/m
Size	W10.6xH11.2mm
Lumen Output*	750 lm/m
Fixture Efficiency	75.0 lm/w
CRI	90
Color Temperature	2700K/3000K/4000K
Beam Angle	120°
Source Type	Citizen COB LED
Power Factor	-
Shielding Angle	60°
Control Method	Not dimmable, Phase-cut dimming, 0/1-10V dimming, DALI dimming

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	X
Product Dimensions	W10.6xH11.2 mm
Weight	X
Package Size	X
Carton Size	X

Safety Class	Class II
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L70/B10-Ta25°
IP Rating	IP20
Housing Material	Extruded Aluminium
Housing Color	Matt white, Matt black, Customized color
Warranty	3 years

*Lumen output measured @ 2700K, 15° optics, ambient temperature 25°C

Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
07.0102	YW - Matt white YB - Matt black XX - Customized Color	10 - 10W	90	27 - 2700K 30 - 3000K 40 - 4000K	120-120°	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector

Example: 07.0102YW109027120F0

