

Product Specifications

Input Voltage		AC 220 -240V, 50-60Hz	
Fixture Power	30W	45W	60W
Size	L1198xW150xH40mm	L1788xW150xH40mm	L2388xW150xH40mm
Lumen Output*	2850 lm	4275 lm	5700 lm
Fixture Efficiency	95.0 lm/w	95.0 lm/w	95.0 lm/w
CRI	90		
Color Temperature	3000K/4000K/5000K		
Beam Angle	MPO		
Source Type	Citizen COB LED		
Power Factor	>0.9		
Shielding Angle	60°		
Control Method	Not dimmable, 0/1-10V dimming, DALI dimming		

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	/
Product Dimensions	L1198/1788/2388*W150*H40 mm
Weight	/
Package Size	/
Carton Size	/

Safety Class	Class I
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L90/B10-Ta25°
IP Rating	IP20
Housing Material	Extruded Aluminium
Housing Color**	RAL 9006, RAL 9016, RAL 9005, RAL 1035
Warranty	3 years

*Lumen output measured @ 2700K, ambient temperature 25°C

**RAL 9006 White aluminium, RAL 9016 Traffic white, RAL 9005 Jet black, RAL 1035 Pearl beige


Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
06.4020	YW - Matt white YB - Matt black XX - Customized Color	30 - 30W	90	30 - 3000K 40 - 4000K 50 - 5000K	MPO	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector

Example: 06.4020YW309030MPOF0

Photometric Distribution

30W MPO 3000K



Accessories



Suspension Kit