

Continuous connection

Product Specifications

Input Voltage	AC 220 -240V, 50-60Hz	
Fixture Power	28W	48W
Size	L1200xW43xH66 mm	L1800xW43xH66 mm
Lumen Output*	1800 lm	3150 lm
Fixture Efficiency	64.2 lm/w	65.6 lm/w
CRI	90	
Color Temperature	3000K/4000K/5000K	
Beam Angle	30°/45°/110°	
Source Type	Citizen COB LED	
Power Factor	>0.9	
Shielding Angle	60°	
Control Method	Not dimmable, 0/1-10V dimming, DALI dimming	

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	/
Product Dimensions	L1200/1800*W43*H66 mm
Weight	/
Package Size	/
Carton Size	/

Safety Class	Class I
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L90/B10-Ta25°
IP Rating	IP20
Housing Material	Extruded Aluminium
Housing Color**	RAL 9006, RAL 9016, RAL 9005, RAL 1035
Warranty	3 years

*Lumen output measured @ 2700K, ambient temperature 25°C

**RAL 9006 White aluminium, RAL 9016 Traffic white,
RAL 9005 Jet black, RAL 1035 Pearl beige


Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
06.1010	YW - Matt white YB - Matt black XX - Customized Color	028 - 28W 048 - 48W	90	30 - 3000K 40 - 4000K 50 - 5000K	30 - 30° 45 - 45° NN - 110°	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector


Example: 06.1010YW028903030F0

Photometric Distribution


28W 30° 3000K



28W 45° 3000K



28W 110° 3000K



Accessories



Fastenings



Suspension Kit