


Continuous connection

Product Specifications

Input Voltage	AC 220 -240V, 50-60Hz		
Fixture Power	30W	48W	72W
Size	L1148xW45xH76 mm	L1722xW45xH76 mm	L2296xW45xH76 mm
Lumen Output*	2300 lm	3450 lm	4650 lm
Fixture Efficiency	76.6 lm/w	71.8 lm/w	64.6 lm/w
CRI	90		
Color Temperature	3000K/4000K/5000K		
Beam Angle	30°/50°/Rectangular/MPO		
Source Type	Citizen COB LED		
Power Factor	>0.9		
Shielding Angle	60°		
Control Method	Not dimmable, 0/1-10V dimming, DALI dimming		

MacAdam Ellipse	<3 SDCM
CCT Tolerance	± 100 K
UGR	/
Product Dimensions	L1148/1722/2296*W45*H76 mm
Weight	/
Package Size	/
Carton Size	/

Safety Class	Class I
Ambient Temperature	-20°C-50°C
Storage Temperature	-20°C-50°C
Lumen Maintenance	-20°C-50°C, LED 50000H L90/B10-Ta25°
IP Rating	IP20
Housing Material	Extruded Aluminium
Housing Color**	RAL 9006, RAL 9016, RAL 9005, RAL 1035
Warranty	3 years

*Lumen output measured @ 2700K, ambient temperature 25°C

**RAL 9006 White aluminium, RAL 9016 Traffic white, RAL 9005 Jet black, RAL 1035 Pearl beige


Ordering code

NO.	Housing color	Watt	CRI	CCT	Beam Angle	Control Method	Reflector
06.0010	YW - Matt white YB - Matt black XX - Customized Color	030 - 30W 048 - 48W 072 - 72W	90	30 - 3000K 40 - 4000K 50 - 5000K	30 - 30° 50 - 50° Rectangular MPO	F - Standard on-off P - Phase dimming A - 0/1-10V dimming D - Dali dimming	0 - No Reflector


Example: 06.0010YW030903030F0

Photometric Distribution


30W 30° 3000K




30W 50° 3000K



30W Rectangular 3000K



30W MPD 3000K



Accessories



Fastenings



Recessed Kit



Suspension Kit



Ceiling-mounted Kit